

MÖLLER-CHEMIE STEINPFLEGEMITTEL GmbH
ZIEGELTALSTRASSE 2
D-93346 IHRLEINSTEIN
TELEFON 09441-176940
TELEFAX 09441-1769499
www.moellerstonecare.eu
info@moellerstonecare.eu

MOELLER STONE CARE



PRODUCT SPECIFICATION

HMK® R152 - OIL AND WAX REMOVER

- **Special cleaner for removing oil, grease and stains caused by mastic sealers.**
 - **Begins working on contact to remove stains from all natural and artificial stone in all finishes, including polished.**
 - **For interior and exterior use.**

HMK® R152 is an active cleaning poultice that removes oil, wax and grease stains as well as cement smears and mineral deposits from all natural and artificial stone, ceramic and concrete. HMK® R152 also removes dirt and stains from tile edges caused by, among other things, the application of unsuitable grout and mastic sealers. The poultice penetrates up to 2 cm in depth and is safe for use on polished and fine honed surfaces. For interior and exterior use.

Important: Whilst the HMK® R152 poultice is drying protect the area from exposure to direct sunlight and wind. Do not apply to rubber, plastics, lacquered or varnished surfaces and solvent intolerant materials. Remove all foodstuffs from the area to be treated before work is commenced.

Instructions: If under floor heating exists, switch it off and allow the surface to cool. Apply HMK® R152 onto the surface with a putty knife or spatula and work into the surface with a brush. Thereafter add more HMK® R152 to ensure that there is a layer of at least 5mm of poultice. Once dry (this can take up to 12 hours) brush off the hardened poultice but do not scrape off as this can damage the surface. After removing all the poultice scrub the area with HMK® R155 Intensive Cleaner - acid free diluted about 1:20 with clean water, using a scrubbing brush, stiff brush or suitable pad. Remove the dirty liquid and rinse the area thoroughly with clean water. For deeply ingrained or tough stains a second or third treatment may be necessary.

Drying time: Dependent upon room temperature and ventilation, around 10 to 12 hours.

To remove stains from tile edges; thoroughly remove the old grout or mastic sealer and apply HMK® R152 into the fully opened joint and onto the surface as instructed above. After the cleaning process is completed, regrout to the manufacturers specification.

Coverage: About 0,2m²/litre.

Warning: Chemical product. Contains solvent combined with solid matter. Keep out of the reach of children.

Packaging: 12 x 0,25 litre tins/box; 12 x 0,75 litre tins/box.

Storage: Store in a cool dry place and keep lid tightly closed.

Testing: Always test the product in an inconspicuous area to evaluate suitability, coverage and performance. Do not use the product in temperatures below 12° and above 25°C.

Limitation of liability: The liability of HMK® Moeller Stone Care for defective products and any claims for damages whatsoever is limited to the purchase price of the products. HMK® Moeller Stone Care shall not be liable for any consequential damages. No other warranty or representation is made or implied.